

vessel specification supplied by

GreenSwift & SeaRoach JV

Captain Jim Roach, jim.roach@searoach.com, 0705 588 8177
Tari Best, Tari@greenswiift.com, 0802 308 4933



File #: NDSVIK

UTILITY BOAT



Characteristics

Overall length	96.785ft	29.78m
Beam	25.74ft	7.92m
Depth	8.03ft	2.47m
Light Draft	6.93ft	2.13m
Max Draft	10.01ft	3.08m
GRT		74 tons
NRT		54 tons
Deck space	12.2m x 6.15m-75.03m	

Capacities

Deck cargo	67.7tons
Fuel oil	55m3
Pot water	70m3
Drill water	50m

Transfer rate

Drill water	70m3 at 150ft head
Fuel oil	55m3 at 150 ft head

Registration

Port	Panama
Builder	Port Brownsville Shipyard Texas

Machinery

Mains Engines	Engine Type GM 16 VT
Generators	Engine Type GM 4-71 2 x 50 KVA

Accommodation

State Rooms	(3) Cabins
Certified to carry	28
Airconditioning/Heating	A/C

Performance

Max speed	11 knotsat 5.64T /24 Hr
Economical	10 knots at 4.80T/24 Hr
Range	2,640 @ 1650 RPM
Bollard pull	12 ton

Vessel mooring

Windlass	300m of 20mm wire
Anchors	500kg high holding anchor
Chains	

Electronics

Radar	1 X FURUNO
Radios	1 x SSB 3 x VHF 1 x VHF portable
Compass	1 x Magnetic

Special equipment and additional comments

The information to the best of our knowledge is believed to be correct,we advise the services of an independent surveyor